

Tamara Munzner

Vision/Color II, Rasterization

Week 6, Mon Feb 8

http://www.ugrad.cs.ubc.ca/~cs314/vjan2010

Events this week

Schlumberger Info Session

Date: Mon., Feb 8
Time: 5:30 pm
Location: HENN Rm 201

Masters of Digital Media Program Info Session

Date: Thurs., Feb 11
Time: 12:30 - 1:30 pm
Location: DMP 201

Finding a Summer Job or Internship Info Session

Date: Wed., Feb 10
Time: 12 pm
Location: X836

Reminder: Co-op Deadline


Date: Fri., Feb 12
Submit application to Fiona at Rm X241 by 4:30 pm

News


- TA office hours in lab for P2/H2 questions this week
 - Mon 3-5 (Shailen)
 - Tue 3:30-5 (Kai)
 - Wed 3-5 (Shailen)
 - Thu 3-5 (Kai)
 - Fri 2-4 (Garrett)
- again - start now, do not put off until late in break!

Review: Trichromacy and Metamers

- three types of cones
- color is combination of cone stimuli
 - metamer: identically perceived color caused by very different spectra




Review: Measured vs. CIE Color Spaces



- measured basis
 - monochromatic lights
 - physical observations
 - negative lobes
- transformed basis
 - "imaginary" lights
 - all positive, unit area
 - Y is luminance


Review: Chromaticity Diagram

- plane of equal brightness showing chromaticity




Device Color Gamuts


- gamut is polygon, device primaries at corners
 - defines reproducible color range
 - X, Y, and Z are hypothetical light sources, no device can produce entire gamut



Display Gamuts




Projector Gamuts



From A Field Guide to Digital Color, © A.K. Peters, 2003


Gamut Mapping

- how to handle colors outside gamut?
 - one way: construct ray to white point, find closest displayable point within gamut




RGB Color Space (Color Cube)

- define colors with (r, g, b) amounts of red, green, and blue
 - used by OpenGL
 - hardware-centric
- RGB color cube sits within CIE color space
 - subset of perceivable colors
 - scale, rotate, shear cube



HSV Color Space

- more intuitive color space for people
 - H = Hue
 - dominant wavelength, "color"
 - S = Saturation
 - how far from grey/white
 - V = Value
 - how far from black/white
 - also: brightness B, intensity I, lightness L



HSI/HSV and RGB

- HSV/HSI conversion from RGB not expressible in matrix
 - H=hue same in both
 - V=value is max, I=intensity is average


$$H = \cos^{-1} \left[\frac{\frac{1}{2}[(R-G) + (R-B)]}{\sqrt{(R-G)^2 + (R-B)(G-B)}} \right] \text{ if } (B > G), H = 360 - H$$

$$\text{HSI: } S = 1 - \frac{\min(R,G,B)}{I} \quad I = \frac{R+G+B}{3}$$

$$\text{HSV: } S = 1 - \frac{\min(R,G,B)}{V} \quad V = \max(R,G,B)$$


YIQ Color Space

- color model used for color TV
 - Y is luminance (same as CIE)
 - I & Q are color (not same I as HSI!)
 - using Y backwards compatible for B/W TVs
 - conversion from RGB is linear
 - expressible with matrix multiply
- $$\begin{bmatrix} Y \\ I \\ Q \end{bmatrix} = \begin{bmatrix} 0.30 & 0.59 & 0.11 \\ 0.60 & -0.28 & -0.32 \\ 0.21 & -0.52 & 0.31 \end{bmatrix} \begin{bmatrix} R \\ G \\ B \end{bmatrix}$$
- green is much lighter than red, and red lighter than blue




Luminance vs. Intensity

- luminance
 - Y of YIQ
 - $0.299R + 0.587G + 0.114B$
 - captures important factor
- intensity/brightness
 - I/V/B of HSI/HSV/HSB
 - $0.333R + 0.333G + 0.333B$
 - not perceptually based




Opponent Color

- definition
 - achromatic axis
 - R-G and Y-B axis
 - separate lightness from chroma channels
- first level encoding
 - linear combination of LMS
 - before optic nerve
 - basis for perception
 - "color blind" = color deficient
 - degraded/no acuity on one axis
 - 8%-10% men are red/green deficient



vischeck.com


- simulates color vision deficiencies



17

Color/Lightness Constancy

- color perception depends on surrounding
 - colors in close proximity
 - simultaneous contrast effect
- illumination under which the scene is viewed



18

Color/Lightness Constancy



Image courtesy of John McCann

19

Color/Lightness Constancy




Image courtesy of John McCann

20

Color Constancy

- automatic "white balance" from change in illumination
- vast amount of processing behind the scenes!
- colorimetry vs. perception



From Color Appearance Models, fig 8-1

22

Stroop Effect

- red
- blue
- orange
- purple
- green

22

Stroop Effect

- blue
- green
- purple
- red
- orange


- interplay between cognition and perception

23

Rasterization

24

Rendering Pipeline



25


Scan Conversion - Rasterization

- convert continuous rendering primitives into discrete fragments/pixels
 - lines
 - midpoint/Bresenham
 - triangles
 - flood fill
 - scanline
 - implicit formulation
 - interpolation


26

Scan Conversion

- given vertices in DCS, fill in the pixels
- display coordinates required to provide scale for discretization



27



Basic Line Drawing

$$y = mx + b$$

$$y = \frac{(y_1 - y_0)}{(x_1 - x_0)}(x - x_0) + y_0$$


- goals
 - integer coordinates
 - thinnest line with no gaps
- assume
 - $x_0 < x_1$, slope $0 < dy/dx < 1$
 - one octant, other cases symmetric
- how can we do this more quickly?

```

Line ( x0, y0, x1, y1 )
begin
float dx, dy, x, y, slope;
dx ← x1 - x0;
dy ← y1 - y0;
slope ← dy/dx;
y ← y0;
for x from x0 to x1 do
begin
PlotPixel ( x, Round ( y ) );
y ← y + slope;
end;
end;
    
```

Midpoint Algorithm

- we're moving horizontally along x direction
 - only two choices: draw at current y value, or move up vertically to y+1?
 - check if midpoint between two possible pixel centers above or below line
- candidates
 - top pixel: (x+1, y+1)
 - bottom pixel: (x+1, y)
- midpoint: (x+1, y+.5)
- check if midpoint above or below line
 - below: pick top pixel
 - above: pick bottom pixel
- key idea behind Bresenham
 - [demo]



29

Making It Fast: Reuse Computation

- midpoint: if $f(x+1, y+.5) < 0$ then $y = y+1$
 - on previous step evaluated $f(x-1, y-.5)$ or $f(x-1, y+.05)$
 - $f(x+1, y) = f(x, y) + (y_0 - y_1)$
 - $f(x+1, y+1) = f(x, y) + (y_0 - y_1) + (x_1 - x_0)$
- ```

y=y0
d = f(x0+1, y0+.5)
for (x=x0; x <= x1; x++) {
draw(x, y);
if (d<0) then {
y = y + 1;
d = d + (x1 - x0) + (y0 - y1)
} else {
d = d + (y0 - y1)
}
}

```

30

## Making It Fast: Integer Only

- avoid dealing with non-integer values by doubling both sides
- ```

y=y0
2d = 2 * (y0-y1)(x0+1) +
(x1-x0)(2y0+1) +
2x0y1 - 2x1y0
for (x=x0; x <= x1; x++) {
draw(x, y);
if (d<0) then {
y = y + 1;
d = d + (x1 - x0) +
(y0 - y1)
} else {
d = d + 2(y0 - y1)
}
}
    
```

31


Rasterizing Polygons/Triangles

- basic surface representation in rendering
- why?
 - lowest common denominator
 - can approximate any surface with arbitrary accuracy
 - all polygons can be broken up into triangles
 - guaranteed to be:
 - planar
 - triangles - convex
 - simple to render
 - can implement in hardware

32

Triangulating Polygons


- simple convex polygons
 - trivial to break into triangles
 - pick one vertex, draw lines to all others not immediately adjacent
 - OpenGL supports automatically
 - `glBegin(GL_POLYGON) ... glEnd()`
- concave or non-simple polygons
 - more effort to break into triangles
 - simple approach may not work
 - OpenGL can support at extra cost
 - `gluNewTess(), gluTessCallback(), ...`



33


Problem

- input: closed 2D polygon
- problem: fill its interior with specified color on graphics display
- assumptions
 - simple - no self intersections
 - simply connected
- solutions
 - flood fill
 - edge walking



Flood Fill


- simple algorithm
 - draw edges of polygon
 - use flood-fill to draw interior



35

Flood Fill

- start with **seed point**
- recursively set all neighbors until boundary is hit



36

Flood Fill

- draw edges
- run:



```

FloodFill(Polygon P, int x, int y, Color C)
if not (OnBoundary(x,y,P) or Colored(x,y,C))
begin
    PlotPixel(x,y,C);
    FloodFill(P,x+1,y,C);
    FloodFill(P,x,y+1,C);
    FloodFill(P,x,y-1,C);
    FloodFill(P,x-1,y,C);
end;
            
```
- drawbacks?

37

Flood Fill Drawbacks


- pixels visited up to 4 times to check if already set
- need per-pixel flag indicating if set already
 - must clear for every polygon!



38

Scanline Algorithms


- scanline**: a line of pixels in an image
 - set pixels inside polygon boundary along horizontal lines one pixel apart vertically



39

General Polygon Rasterization

- how do we know whether given pixel on scanline is inside or outside polygon?




40

General Polygon Rasterization

- idea: use a **parity test**

```


for each scanline
    edgeCnt = 0;
    for each pixel on scanline (1 to x)
        if (oldpixel->newpixel crosses edge)
            edgeCnt++;
        // draw the pixel if edgeCnt odd
        if (edgeCnt % 2)
            setPixel(pixel);
            
```



41

Making It Fast: Bounding Box


- smaller set of candidate pixels
 - loop over xmin, xmax and ymin,ymax instead of all x, all y



42

Triangle Rasterization Issues

- moving slivers
- shared edge ordering



43

Triangle Rasterization Issues

- exactly which pixels should be lit?**
 - pixels with centers inside triangle edges
- what about pixels exactly on edge?**
 - draw them: order of triangles matters (it shouldn't)
 - don't draw them: gaps possible between triangles
- need a consistent (if arbitrary) rule
 - example: draw pixels on left or top edge, but not on right or bottom edge
 - example: check if triangle on same side of edge as offscreen point

44

Interpolation


Interpolation During Scan Conversion

- drawing pixels in polygon requires interpolating many values between vertices
 - r,g,b colour components
 - use for shading
 - z values
 - u,v texture coordinates
 - N_x, N_y, N_z surface normals
- equivalent methods (for triangles)
 - bilinear interpolation
 - barycentric coordinates

45

Bilinear Interpolation


- interpolate quantity along L and R edges, as a function of y
 - then interpolate quantity as a function of x



47


Barycentric Coordinates

- non-orthogonal coordinate system based on triangle itself
 - origin: P_1 , basis vectors: $(P_2 - P_1)$ and $(P_3 - P_1)$



48

Barycentric Coordinates




Barycentric Coordinates

- non-orthogonal coordinate system based on triangle itself
- origin: P_1 , basis vectors: $(P_2 - P_1)$ and $(P_3 - P_1)$

$$P = P_1 + \beta(P_2 - P_1) + \gamma(P_3 - P_1)$$


$$P = (1 - \beta - \gamma)P_1 + \beta P_2 + \gamma P_3$$

$$P = \alpha P_1 + \beta P_2 + \gamma P_3$$



Using Barycentric Coordinates

- weighted combination of vertices
- smooth mixing
- speedup
 - compute once per triangle



$$P = \alpha \cdot P_1 + \beta \cdot P_2 + \gamma \cdot P_3$$


$$\alpha + \beta + \gamma = 1$$

$$0 \leq \alpha, \beta, \gamma \leq 1 \text{ for points inside triangle}$$

"convex combination of points"

Deriving Barycentric From Bilinear

- from bilinear interpolation of point P on scanline




$$P_L = P_2 + \frac{d_1}{d_1 + d_2}(P_3 - P_2)$$

$$= (1 - \frac{d_1}{d_1 + d_2})P_2 + \frac{d_1}{d_1 + d_2}P_3 =$$

$$= \frac{d_2}{d_1 + d_2}P_2 + \frac{d_1}{d_1 + d_2}P_3$$

Deriving Barycentric From Bilinear

- similarly




$$P_R = P_2 + \frac{b_1}{b_1 + b_2}(P_1 - P_2)$$

$$= (1 - \frac{b_1}{b_1 + b_2})P_2 + \frac{b_1}{b_1 + b_2}P_1 =$$

$$= \frac{b_2}{b_1 + b_2}P_2 + \frac{b_1}{b_1 + b_2}P_1$$

Deriving Barycentric From Bilinear

- combining



$$P = \frac{c_2}{c_1 + c_2} \cdot P_L + \frac{c_1}{c_1 + c_2} \cdot P_R$$

$$P_L = \frac{d_2}{d_1 + d_2} P_2 + \frac{d_1}{d_1 + d_2} P_3$$

$$P_R = \frac{b_2}{b_1 + b_2} P_2 + \frac{b_1}{b_1 + b_2} P_1$$

- gives

$$P = \frac{c_2}{c_1 + c_2} \left(\frac{d_2}{d_1 + d_2} P_2 + \frac{d_1}{d_1 + d_2} P_3 \right) + \frac{c_1}{c_1 + c_2} \left(\frac{b_2}{b_1 + b_2} P_2 + \frac{b_1}{b_1 + b_2} P_1 \right)$$

Deriving Barycentric From Bilinear

- thus $P = \alpha P_1 + \beta P_2 + \gamma P_3$ with

$$\alpha = \frac{c_1}{c_1 + c_2} \frac{b_1}{b_1 + b_2}$$

$$\beta = \frac{c_2}{c_1 + c_2} \frac{d_2}{d_1 + d_2} + \frac{c_1}{c_1 + c_2} \frac{b_2}{b_1 + b_2}$$

$$\gamma = \frac{c_2}{c_1 + c_2} \frac{d_1}{d_1 + d_2}$$

- can verify barycentric properties

$$\alpha + \beta + \gamma = 1, \quad 0 \leq \alpha, \beta, \gamma \leq 1$$

Computing Barycentric Coordinates

- 2D triangle area
- half of parallelogram area
 - from cross product

$$A = A_{P_1} + A_{P_2} + A_{P_3}$$

$$\alpha = A_{P_1} / A$$

$$\beta = A_{P_2} / A$$

$$\gamma = A_{P_3} / A$$

