LIGHTING / "SHADING"


Models the interaction of light with surfaces. Generates a per (pixel/vertex) colour.

FACTORS:

- Light sources
 - Location, type & color
- Surface materials
 - How surfaces reflect light
- Transport of light
 - · How light moves in a scene
- Viewer position
- How can we do this in the pipeline?



THE RENDERING PIPELINE




ILLUMINATION MODELS/ALGORITHMS

Local illumination – Fast

 assumes single-bounce path: light – surface – eye

Global illumination – Slow


• (More) Physically based computation of light transport throughout the scene





THE BIG PICTURE


- Light: energy in a range of wavelengths
 - White light all wavelengths
 - Colored (e.g. red) subset of wavelengths
- Surface "color" reflected wavelength
 - White reflects all lengths
 - Black absorbs everything
 - Colored (e.g. red) absorbs all but the reflected color
- Multiple light sources add (energy sums)





- big simplification: just work with three "wavelengths": R,G,B which roughly correspond to the three types of cone-cells in the human eye.
 - white light (1,1,1) x yellow surf (0.8,0.8,0) = yellow visible (0.8,0.8,0)
 - yellow light (1,1,0) x cyan surf (0,1,1) = green visible(0,1,0)


MATERIALS

- Surface reflectance:
 - Illuminate surface point with a ray of light from different directions
 - How much light is reflected in each outgoing direction?











Intuition: Brightness depends on the angle of the surface with respect to the incoming light direction. Sharper angles mean that the surface receives less light.






 $N \cdot L = \cos(\theta)$

only consider angles from 0-90, i.e., if N.L negative, then set to zero






simple hack that provides a default minimal illumination **AMBIENT TERM** $I_a k_a + \sum I_L k_d (N \cdot L) + I_L k_s (R \cdot V)^n$ scene property L ambient light color surface property: ambient color k_a 0.2 = 0.2 0 ambient term with ambient light without ambient light apply individually to RGB components

see: http://www.realtimerendering.com/teapot/

DIFFUSE TERM

The apparent brightness (the reflected radiance) *is independent* of the viewing direction.

Two correct interpretations:




[http://www.oceanopticsbook.info/view/surfaces/lambertian_brdfs]

SPECULAR (PHONG) TERM


$$I_a k_a + \sum_L I_L k_d (N \cdot L) + I_L k_s (R \cdot V)^n$$
"shininess"
 $R \cdot V = \cos(\alpha)$

Many surfaces are not perfect mirrors, but still reflect much light in the general direction of the reflected ray. As we get further away from the reflected ray, we see less light being reflected in those directions.




SPECULAR TERM: COMPUTATIONS


• Geometry of specular (perfect mirror) reflection



PHONG EXAMPLES

varying light position





The Phong specular term is an emperical model, i.e., not physics-based.

It generally produces a "plastic" appearance.


ALTERNATIVE: BLINN-PHONG MODEL

(Jim Blinn, 1977)

• Variation with better physical interpretation

• h: halfway vector; r: roughness

$$I_{specular} = k_s \cdot (\mathbf{h} \cdot \mathbf{n})^{1/r} \cdot I_{light}; \text{ with } \mathbf{h} = (\mathbf{l} + \mathbf{v})/2$$



LIGHT SOURCE TYPES

- Point Light
 - light originates at a point
 - defined by location only
- Directional Light (point light at infinity)
 - light rays are parallel
 - Rays hit a planar surface at identical angles
 - defined by direction only
- Spot Light
 - point light with limited angles
 - defined by location, direction, and angle range
- Light source fall-off: intensity drops with distance squared

multily by 1-2

I is constant



Area $4\pi(2r)^2$

WHICH LIGHTS/MATERIALS ARE USED HERE?



LIGHT AND MATERIAL SPECIFICATION

- Light source: amount of RGB light emitted
 - value = intensity per channel e.g., (1.0,0.5,0.5)
 - every light source emits ambient, diffuse, and specular light
- Materials: amount of RGB light reflected
 - value represents percentage reflected e.g., (0.0,1.0,0.5)
- Interaction: multiply components
 - Red light (1,0,0) x green surface (0,1,0) = black (0,0,0)

NOTES ON SHADING

- Typically compute lighting model in VCS. Therefore need:
 VCS Vertex Coordinates, VCS Normals, VCS Light Positions
- How often to compute the lighting model?





Image © Intergraph Computer Systems

GLOBAL ILLUMINATION






SUBSURFACE SCATTERING







QUESTIONS

• Give the Phong equation parameters that are needed to render a shiny yellow material with a single white light.

$$I = I_a k_a + I_L k_d (N \cdot L) + I_L k_s (R \cdot V)^n$$

- What is the colour of the darkest pixel this model can produce?
- What is the colour of the brightest pixel this model can produce?